

Part No	Appox.Length mm(inch)	Appox.Width mm(inch)	Max.Bundle Dia mm(inch)	Min. Loop Tensile Strength N(lbs)
FZMSP7X150	150(5.9)	7(0.276)	33(1.3)	1120(252)
FZMSP7X225	225(8.86)		57(2.2)	
FZMSP7X300	300(11.8)		81(3.2)	
FZMSP7X400	400(15.7)		92(3.6)	
FZMSP7X490	490(19.3)		141(5.6)	
FZMSP7X550	550(21.7)		161(6.3)	
FZMSP7X600	600(23.6)		176(6.9)	
FZMSP7X650	650(25.6)		192(7.6)	
FZMSP7X700	700(27.6)		208(8.2)	
FZMSP7X750	750(29.5)		224(8.8)	
FZMSP7X800	800(31.5)		240(9.4)	
FZMSP12X150	150(5.9)		12(0.472)	
FZMSP12X225	225(8.86)	57(2.2)		
FZMSP12X300	300(11.8)	81(3.2)		
FZMSP12X335	335(13.2)	92(3.6)		
FZMSP12X400	400(15.7)	113(4.4)		
FZMSP12X450	450(17.7)	129(5.1)		
FZMSP12X490	490(19.3)	141(5.6)		
FZMSP12X550	550(21.7)	161(6.3)		
FZMSP12X600	600(23.6)	176(6.9)		
FZMSP12X650	650(25.6)	192(7.6)		
FZMSP12X700	700(29.5)	208(8.2)		
FZMSP12X750	750(29.5)	224(8.8)		
FZMSP12X800	800(31.5)	240(9.4)		



High corrosion resistant ,Multi-lock type

Good loop tensile strength can touch 250Lbs

Manufactured from 316# & 304# stainless steel

Outdoor and Indoor use

Ideal for used in telecommunication, electricity, shipbuilding and oil gas industry

Working temperature:-40°C-85°C