



| Part No | Approx.Length mm(inch) | Approx.Width mm(inch) | Max.Bundle Dia mm(inch) | Min. Loop Tensile Strength N(lbs) | | |
|---------------|---------------------------|--------------------------|----------------------------|---|----------|----------|
| FZGSP-4.6X150 | 150(5.9) | 4.6(0.181) | 37(1.46) | 600(135) | | |
| FZGSP-4.6X200 | 200(7.87) | | 50(1.97) | | | |
| FZGSP-4.6X250 | 250(9.84) | | 63(2.48) | | | |
| FZGSP-4.6X300 | 300(11.8) | | 76(2.99) | | | |
| FZGSP-4.6X350 | 350(13.78) | | 89(3.5) | | | |
| FZGSP-4.6X400 | 400(15.75) | | 102(4.02) | | | |
| FZGSP-4.6X450 | 450(17.72) | | 115(4.53) | | | |
| FZGSP-4.6X500 | 500(19.69) | | 128(5.04) | | | |
| FZGSP-4.6X550 | 550(21.65) | | 141(5.55) | | | |
| FZGSP-4.6X600 | 600(23.62) | | 154(6.06) | | | |
| FZGSP-7.9X150 | 150(5.9) | | 7.9(0.311) | | 37(1.46) | 800(180) |
| FZGSP-7.9X200 | 200(7.87) | | | | 50(1.97) | |
| FZGSP-7.9X250 | 250(9.84) | 63(2.48) | | | | |
| FZGSP-7.9X300 | 300(11.8) | 76(2.99) | | | | |
| FZGSP-7.9X350 | 350(13.78) | 89(3.5) | | | | |
| FZGSP-7.9X400 | 400(15.75) | 102(4.02) | | | | |
| FZGSP-7.9X450 | 450(17.72) | 115(4.53) | | | | |
| FZGSP-7.9X500 | 500(19.69) | 128(5.04) | | | | |
| FZGSP-7.9X550 | 550(21.65) | 141(5.55) | | | | |
| FZGSP-7.9X600 | 600(23.62) | 154(6.06) | | | | |
| FZGSP-7.9X650 | 650(25.59) | 167(6.57) | | | | |
| FZGSP-7.9X700 | 700(27.56) | 180(7.09) | | | | |
| FZGSP-7.9X750 | 750(29.53) | 191(7.52) | | | | |
| FZGSP-7.9X800 | 800(31.5) | 193(7.59) | | | | |
| FZGSP-12X150 | 150(5.9) | 12(0.472) | 37(1.46) | 1200(270) | | |
| FZGSP-12X200 | 200(7.87) | | 50(1.97) | | | |
| FZGSP-12X250 | 250(9.84) | | 63(2.48) | | | |
| FZGSP-12X300 | 300(11.8) | | 76(2.99) | | | |
| FZGSP-12X350 | 350(13.78) | | 89(3.5) | | | |
| FZGSP-12X400 | 400(15.75) | | 102(4.02) | | | |
| FZGSP-12X450 | 450(17.72) | | 115(4.53) | | | |
| FZGSP-12X500 | 500(19.69) | | 128(5.04) | | | |
| FZGSP-12X550 | 550(21.65) | | 141(5.55) | | | |
| FZGSP-12X600 | 600(23.62) | | 154(6.06) | | | |
| FZGSP-12X650 | 650(25.59) | | 167(6.57) | | | |
| FZGSP-12X700 | 700(27.56) | | 180(7.09) | | | |
| FZGSP-15X200 | 200(7.87) | 15(0.59) | 50(1.97) | 1500(337) | | |
| FZGSP-15X250 | 250(9.84) | | 63(2.48) | | | |
| FZGSP-15X300 | 300(11.8) | | 76(2.99) | | | |
| FZGSP-15X350 | 350(13.78) | | 89(3.5) | | | |
| FZGSP-15X400 | 400(15.75) | | 102(4.02) | | | |
| FZGSP-15X450 | 450(17.72) | | 115(4.53) | | | |
| FZGSP-15X500 | 500(19.69) | | 128(5.04) | | | |
| FZGSP-15X550 | 550(21.65) | | 141(5.55) | | | |
| FZGSP-15X600 | 600(23.62) | | 154(6.06) | | | |
| FZGSP-15X650 | 650(25.59) | | 167(6.57) | | | |
| FZGSP-15X700 | 700(27.56) | | 180(7.09) | | | |
| FZGSP-15X750 | 750(29.53) | | 191(7.52) | | | |
| FZGSP-15X800 | 800(31.5) | 193(7.59) | | | | |
| FZGSP-15X1000 | 1000(39.37) | 206(8.11) | | | | |



Stainless Steel cable ties are designed to secure hoses, cables, poles, pipes and more harsh environment conditions may adversely affect the building applications.

Used where corrosion, vibration, weathering, radiation and temperature extremes are a concern, DIGITAL SYMBOL stainless steel cable ties could be used in virtually any indoor, outdoor and any underground applications.

UV resistant, Low Smoke, Non-flammability, Halogen-free, operation temperature -40°C-150°C high resistance to acetic acid, alkali acid, sulphuric acid, etc

Material: Stainless Steel 304#, 316#

Coating: 100% Pure Ployester Coated
all colours as per customer's request are available

All length available, length could be cut as per request

