



Part No.	Material	Width		Length		Thickness After Coated		Maximum Diameter Single Wrap		Minimum Loop Tensile Strength (Lbs)
		In	mm	In	mm	In	mm	In	mm	
6.35X152	316 SS	1/4	6.35	6	152	0.045	1.1	1.5	38	75/300
6.35X229	316 SS	1/4	6.35	9	229	0.045	1.1	2.5	63	75/300
6.35X305	316 SS	1/4	6.35	12	305	0.045	1.1	3.4	86	75/300
6.35X457	316 SS	1/4	6.35	18	457	0.045	1.1	5.4	137	75/300
6.35X610	316 SS	1/4	6.35	24	610	0.045	1.1	7.3	185	75/300
9.53X152	316 SS	3/8	9.53	6	152	0.045	1.1	1.5	38	100/500
9.53X229	316 SS	3/8	9.53	9	229	0.045	1.1	2.5	63	100/500
9.53X305	316 SS	3/8	9.53	12	305	0.045	1.1	3.4	86	100/500
9.53X457	316 SS	3/8	9.53	18	457	0.045	1.1	5.4	137	100/500
9.53X610	316 SS	3/8	9.53	24	610	0.045	1.1	7.3	185	100/500
9.53X762	316 SS	3/8	9.53	30	762	0.045	1.1	9.1	231	100/500
9.53X914	316 SS	3/8	9.53	36	914	0.045	1.1	11	280	100/500

Thickness includes coating layer

Single / Double Wrapped

Reusable, All length available, length could be cut as per request

Standard material was 316# grade stainless steel ,304# grade stainless steel could be optional for customer

